

690-008568-US (PAR)

D/99039

Patent Application Papers Of:

Ken Hayward,

Marc J. Krolczyk,

Dawn M. Marchionda,

Thomas L. Wolf, and

James S. Laird

For:

IMAGE TRANSFER SYSTEM

09364959 073099

## IMAGE TRANSFER SYSTEM

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to an image transfer system and, more particularly, to an image transfer system comprising a transfer device which can be operably connected to a computer.

## 2. Prior Art

There are examples in the prior art of image transfer systems comprising an image transfer device coupled to one or more computers. One such example is U.S. Patent 5,798,738 which provides a copying machine print manager system which comprises a terminal connected to a copying machine. Generally, copying machines in the prior are capable of performing only a given set of functions regardless of whether the copying machine is connected to a computer or not.

One object of the present invention is to provide a software and user interface (UI) solution for enriching personal and desktop copier feature sets by utilizing the processing power and memory capacity of a connected personal computer. In accordance with this goal, the present invention addresses the software and UI enablers that allow a document to be scanned at the multifunction device; the device sending the data to the PC to perform enriched copier/printer capabilities such as collation. The PC performs the enriched task and sends the new instructions back to the multifunction device for output. Another object of the present invention provides for initiation of the job to take place at the device, so the user need not know the PC is involved in the process. This invention also addresses feature buttons embedded in

09364959-02099

an UI display on the device which are visible and operational when a PC is connected to the device, and the underlying software that would enable them.

#### SUMMARY OF THE INVENTION

5 In accordance with the first embodiment of the present invention, an electronic assembly is provided. The electronic assembly comprises an image transfer device for reading and transferring an image from a first medium, and a computer. The image transfer device  
10 includes a reader for reading the image on the first medium, and a display. The display displays an image transfer menu for effecting transfer of the image. The computer is removably connected to the image transfer device. When the image transfer device is not connected  
15 to the computer, the image transfer device has a first type of the image transfer menu available for display on the display of the device. When the image transfer device is connected to the computer, the transfer device has a second type of the image transfer menu available  
20 for display on the display of the device.

In accordance with a second embodiment of the present invention, a transfer apparatus is provided. The transfer apparatus has a reader for scanning information disposed on a first medium, and a controller connected to  
25 the reader. The transfer apparatus comprises a connector, and a display. The connector is connected to the controller for removably connecting a computer to the transfer apparatus. The display is connected to the controller for displaying menus comprising features for  
30 operating the transfer apparatus. The display displays a first one of the menus when the computer is not connected to the apparatus. The display displays a second one of the menus when the computer is connected to the

09364959-073099

apparatus. The second menu comprises extended features for operating the apparatus in comparison to the first menu.

5 In accordance with a first method of the present invention, a method for transferring information from a first medium is provided. The method comprises the steps of providing an image transfer device, reading the image on the first medium, sending the image from the transfer device to a computer, automatically manipulating the  
10 image, and automatically sending the manipulated image from the computer to the transfer device. The image transfer device has a scanner for reading an image on the first medium. The manipulated image is sent from the computer to the transfer device without user interaction with the computer. The manipulated image is transferred  
15 from the transfer device to a second medium.

09364959-073099  
20 In accordance with a second method of the present invention, a method for enhancing operating features of a transfer device is provided. The transfer device is adapted for transferring information from a first medium to a second medium. The method comprises the steps of providing a first command menu of the transfer device, connecting a computer to the transfer device, and with the computer enabling the device to display a second  
25 command menu. The first command menu represents a first set of the operating features of the transfer device. The first menu is available for display on a display of the device when the computer is not connected to the transfer device. When the computer is connected to the  
30 transfer device, the computer enables the device to display the second command menu. The second command menu represents a second set of the operating features of the transfer device. The second set of operating features

has expanded operating features in comparison to the first set of operating features of the transfer device.

#### BRIEF DESCRIPTION OF THE DRAWINGS

5 The foregoing aspects and other features of the present invention are explained in the following description, taken in connection with the accompanying drawings, wherein:

Fig. 1 is a schematic diagram of an image transfer system incorporating features of the present invention;

10 Fig. 2 is a schematic diagram showing a computer, and the display, user interface, processor, and memory of an image transfer device of the image transfer system shown in Fig. 1;

15 Fig. 3 is a schematic diagram of the computer, and the display, user interface, processor, and memory of the image transfer device of the system shown in Fig. 1, in accordance with one embodiment of the present invention;

20 Figs. 4-4A are flow charts which graphically illustrate a first method in accordance with the present invention for providing the image transfer device with an enhanced operating menu;

25 Fig. 5 is a schematic diagram of the computer, and the display, user interface, processor, and memory of the image transfer device of the system shown in Fig. 1, in accordance with a second embodiment of the present invention;

30 Fig. 6 is a flow chart which illustrates a second method in accordance with the present invention for providing the image transfer device with an enhanced operating menu;

09364959 "073099  
660E20" 6564959

Fig. 7 is a schematic diagram of the computer, and the display, user interface, processor, and memory of the image transfer device of the system shown in Fig. 1, in accordance with a third embodiment of the present invention;

Fig. 8 is a flow chart which illustrates a third method in accordance with the present invention for providing the image transfer device with an enhanced operating menu; and

Fig. 9 is a flow chart which illustrates an image transfer procedure performed with the image transfer system shown in Fig. 1 in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Fig. 1, there is shown a schematic diagram of an image transfer system 10 incorporating features of the present invention. Although the present invention will be described with reference to the single embodiment shown in the drawings, it should be understood that the present invention can be embodied in many alternate forms of embodiments. In addition, any suitable size, shape or type of elements or materials could be used.

Still referring to Fig. 1, the image transfer system 10 generally includes an image transfer device 12 and a computer 14. The computer 14 is connected to the image transfer device 12 by a cable 36 which is removably mated to a connector 16 of the device 12. The image transfer device 12 generally comprises a reader 18, a central processing unit (CPU) 20, a memory 22, a display 24 and a user interface (UI) 26. Preferably, the device 12 also

09364959-073099

includes a print head 28 and a communication device 30. The reader 18 is adapted to read a printed image on medium 100. The print head 28 is adapted to print an image on medium 102. The communication device 30 is adapted to transmit and receive images between the device 12 and one or more image transfer devices 300 located at remote locations. The reader 18, print head 28, and communication device 30 are connected so that the reader 18 can send information to both the print head 28 and the communication device 30. The communication device 30 can also send information to the print head 28. The CPU 20 is connected to the reader 18, the print head 28, and the communication device 30. The CPU 20 is capable of controlling the operation of the reader 18, the print head 28, and the communication device 30 in response to commands from a user. The user enters commands via the user interface 26 which is connected to the CPU 20. The user selects the commands from a menu displayed on the display 24 of the device 12. The CPU 20 of the image transfer device 12 is connected to the connector 16. The reader 18, print head 28, and communication device 30 are also connected to connector 16. The computer 14 generally includes a processor 32 and a memory 34. The computer 14 may be part of a local area network (not shown). When the computer 14 is connected via cable 36 to the connector 16, the CPU 20 can access the computer processor 32 and memory 34. Also, when the cable 36 is connected to the connector 16, the reader 18, the print head 28, and the communication device 30 are connected to the computer 14. This allows the reader 18 to send information to the computer 14, and allows the computer 14 to send information to the print head 28 and communication device 30 of the image transfer device 12. Thus, the image transfer device may include a computer printer, a copier, a facsimile or an optical scanner capability. In the preferred embodiment, the image

09364959 "073099

transfer device 12 performs as a multi-function device which includes one or more of the aforementioned capabilities. In alternate embodiments the device may have more or less than these four capabilities. The multi-function device 12 of the present invention is capable of operating, at least partially, as a stand alone device when the computer 14 is not connected to the device 12; such as only a copier and/or only a facsimile machine. When the computer 14 is connected to the device 12, the device 12 may use the software and memory of the computer 14 to perform one or more of the enhanced or extended capabilities of the device 12 as will be described in greater detail below.

In particular, the reader 18 of the device 12 is preferably an optical scanner capable of reading an image or pattern embodying information which is disposed on sheet medium 100. In the preferred embodiment, the device 12 has an input area 40 in which the user places the sheet medium 100 for reading by the reader 18. The input area generally includes a cover 41 for covering a glass platen (not shown) upon which the user places the sheet medium 100 with the image face 100A down. The user may place the sheet medium 100 directly on the glass platen or may use a roller system (not shown) within the cover 41 to feed the sheet medium 100 to the glass platen from an input port 40I. The reader 18 is generally located below the glass platen of the input area 40. The reader 18 is orientated relative to the glass platen to scan the surface 100A of the sheet medium 100 placed against the glass platen. In the preferred embodiment, the reader 18 is a movable reader which operates to optically scan the surface 100A of the sheet medium 100 placed on the glass platen. For example, the reader 18 may travel along the length of the sheet medium 100 while scanning laterally across the face 100A of the sheet

09364959-03099



medium 100. In alternate embodiments, the device may have a static reader. In that case, a roller system may transport the sheet medium from the input area over the static reader in order for the reader to read the image on the sheet medium. After the reader 18 has finished reading the images on the sheet medium 100, the sheet medium can be removed manually or output by the roller system (not shown) to an output port 40P of the device 12. During operation, the reader 18 converts the printed image on the sheet medium 100 to binary encoded data which can be sent electronically, as directed by the CPU 20 to the print head 28, or the communication device 30.

The print head 28 is generally capable of receiving an image in the form of binary data and of printing the image on sheet medium 102. The device 12 has an input area 42 for placing sheet medium 102 prior to printing. An output area 44 holds the sheet medium 102 processed by the print head 28. A sheet medium transport system (not shown), such as a roller system for example, inside the device 12 withdraws sheet medium 102 from the input area 42 and transports the sheet medium 102 to the print head 28. The print head 24 prints the image on the sheet medium 102 and the transport system then moves the sheet medium 102 to the output area 44 of the device 12.

The communication device 30 is generally a facsimile transceiver or modem which is coupled to a communication line 302 connecting the device 12 to other image transfer devices 300. The communication line 302 may be a land line such as for example a public switched telephone network (PSTN) or a local area network (LAN) line to which the other transfer devices 300 are connected. However, in alternate embodiments, the communication device may include the capability to communicate with the other image transfer devices over a cellular telephone network.

00364950 65649560

5 The communication device 30 is otherwise adapted to receive the binary data of the image read by the reader 18 and generate signals transmitting the image over the communication line 302 to one or more designated image transfer devices 300. The image transfer devices 300 which receive the signals may then reproduce the transmitted image. The communication device 30 can in turn receive images over the communication line 302 from the image transfer devices 300. The communication device 10 30 demodulates the signals forming the images and then may send the data as directed by the CPU 20 to the print head 28 for printing the images on sheet medium 102.

15 The connector 16 of the image transfer device 12 is preferably a universal bus connector. In alternate embodiments, the connector of the image transfer device may be a parallel port connector. The cable 36 for connecting the computer 14 to the device 12 has a connectorized end 37 adapted to be removably mated to the serial port connector 16. The opposite end 38 of the 20 cable 36, which end is preferably also connectorized, is connected to a suitable input/output port (not shown) of the computer 14. When the computer 14 is connected via cable 36 to the device 12, image data can be sent from the reader 18 to the computer 14. In addition, when the 25 computer 14 is connected to the device 12, data of an image formed with the computer 14 can be sent from the computer 14 to the print head 28 of the device 12. Furthermore, image data generated with the computer 14 may also be sent to the communication device 30 for 30 transmission over communication line 302 to one or more of the image transfer devices 300. Conversely, image data generated by the communication device 28 of images received from one of the remote transfer devices 300, may be sent under the control of the CPU 20 from the 35 communication device 30 to the computer 14.

09364959 "073069

5 The CPU 20 is programmed to control the operation of the reader 18, the print head 28 and the communication device 30. The CPU 20 controls the operational sequence of the reader 18, print head 28 and communication device 30 as well as the flow of data therebetween. For example, when the image transfer device 12 is operating in a copier mode, the CPU 20 energizes the reader 18 to read the image on surface 100A of the sheet medium 100. The CPU 20 directs the data from the reader 18 to the print head 10 28 and queues the print head to print the image read by the reader 18 on sheet medium 102. Concurrent with this, the CPU also operates the transport system transporting the sheet medium 102 from the input area 42 to the print head 28 and then to the output area 44 of the device. 15 When the device 12 is operating in a facsimile sending mode, the CPU 20 operates the communication device 30 to make a connection with selected remote devices 300. The CPU 20 then energizes the reader 18 to read the image on the sheet medium 100 and directs the data to the communication device 30 which sends the data to the 20 remote device 300. In the facsimile standby mode, the CPU 20 operates the communication device 30 to respond to a connection signal from a remote device 300 and form a connection. The CPU 20 may then direct the demodulated image signal received by the communication device 32 to 25 the print head 28 and queue the print head for printing the image on sheet medium 102. The CPU 20 also controls operations of the device 12 when the computer 14 is connected to the device. For instance, when the device 30 12 is in a scanner mode, the CPU 20 energizes the reader 18 and sends the image data from the reader to the computer. When the device 12 is in a printer mode, the CPU 20 queues the print head for printing and directs image data from the computer 14 to the print head 28.

036495 650E40 65649E60

5 The user uses the display 24 and the user interface 26 to  
operate the image transfer device 12. Referring now also  
to Fig. 2, the display 24 of the image transfer device 12  
is preferably a LCD though any other suitable type of  
display may be used. Operation of the display 24 is  
controlled by the CPU 20. The display 24 comprises  
display zones 46 in which the CPU 20 brings up  
operational and device status information on the display  
24. For example, the CPU 20 is capable of counting the  
10 pages processed by the reader 18 and the print head 28  
and may display the reader page count in zone 46A on the  
display and the print head page count in zone 46B of the  
display 24. The CPU 20, in accordance with its  
programming, may further activate LCD pixels of the  
15 display in order to present pre-programmed indicia in  
zone 46C which indicate to the user various housekeeping  
functions of the device 12. Such indicia may include for  
example, a symbol indicating that a paper jam has  
occurred, or a symbol indicating that maintenance should  
20 be performed on a portion of the device 12 such as the  
reader 18 or the print head 24. The CPU 20 may be  
programmed to control the LCD pixels of the display 24 to  
also display messages. The CPU 20 is further programmed  
to display an operating menu 48 on the display 24 of the  
25 transfer device 12. The operating menu comprises  
commands which designate functions of the device 12. In  
the preferred embodiment, the LCD display 24 of the  
device 12 incorporates an active or touch display 50.  
The CPU 20 displays the operating menu 48 of the device  
30 within the touch display 50. The operating menu 48  
includes feature or command buttons 52 disposed on the  
touch display 50. The user may activate and deactivate,  
one or more of the command buttons 52 by touching the  
desired buttons 52 shown on the display 50. The user may  
35 also activate or deactivate the command buttons 52 of the  
operating menu by using the user interface 26 of the

09364959-073099

device 12. As shown in Fig. 2, the user interface 26 generally includes a numerical keypad 54, a track ball 56 and function keys 58 corresponding to the command buttons 52 of the menu on the touch display 50. The track ball 56 allows the user to move a pointer (not shown) which the CPU 20 displays on the display 50. The user may thus select one of the command buttons 52 by moving the pointer to the desired button and striking an enter or register key (not shown) on the user interface 26 which activates or deactivates the button 52. The user may also activate or deactivate a command button 52 by striking a predetermined key 58 on the user interface 26 which corresponds to the desired button 52. In alternate embodiments, the display of the device need not be a touch display, in which case the command features of the operating menu shown on the display may be activated and deactivated by using the keys and track ball of the user interface. The CPU 20 senses activation or deactivation of the command buttons 52 and changes the display 50 to shown that the selected buttons 52 have been activated or deactivated as appropriate. Activation of the command buttons 52 of the operating menu shown on the display 50 sends the commands corresponding to the activated buttons to the CPU 20 which in turn proceeds to control the operation of the device in accordance with the received commands. Deactivation of the command buttons 52 deletes the corresponding operative commands from the CPU 20.

The software used by the CPU 20 is stored in the memory 22 of the device 12. In addition to storing the software used by the CPU 20, the memory 22 may also have memory space for storing data sent from the reader 18, the communication device 30, or the computer 14 when the computer is connected to the device 12. In general, the software stored in the memory 22 includes a default or basic program 200 for operating the image transfer device

12. The basic program is loaded in the CPU 20 when the CPU 20 is initialized and the computer 14 is not connected via cable 36 to connector 16 of the device 12. The basic program 200 has a module 202 which defines the basic operating menu available for display by the CPU 20 on the display 50 when the computer 14 is not connected to the device 12. The basic program 200 also includes a program module 204 which provides instructions to the CPU 20 for controlling the functions of the device 12 corresponding to the commands within the basic operating menu.

One example of the features of the basic operating menu available for display by the CPU 20 as defined by program module 202 are listed in Table 1 below.

1. COPIER					2. FACSIMILE				
II. ORIGINAL TYPE					II. ORIGINAL TYPE				
1. AUTO*	2. TEXT	3. PHOTO	III. MAINTENANCE		1. AUTO*	2. TEXT	3. PHOTO	III. TELEPHONE NUMBERS	
1. CLEAN PRINT HEAD	2. PRINT TEST PAGE	3. ALIGN PRINT HEAD	4. RESET PRINTER	5. INK LEVELS A. Black B. Cyan C. Magenta D. Yellow	NO. 1	NO. 2	NO. 3	NO. 4	NO. 5
					NO. 4	NO. 5	NO. 6	NO. 7	NO. 8
IV. PRINT DEMO					V. DEFAULTS				
1. Feature Defaults A. Save new B. Reset	2. Program Time-out A. 60 sec.* B. 90 sec.	3. Sleep Mode A. 5 min* B. 10 min	4. Paper Size A. Letter* B. A4	5. Reset Factory	1. Feature Defaults A. Save new B. Reset	2. AUTO REDIAL A. 3 min* B. 5 min	2. Program Time-out A. 60 sec.* B. 90 sec.	3. Sleep Mode A. 5 min* B. 10 min	4. Paper Size A. Letter* B. A4
VI. LANGUAGE					VI. LANGUAGE				
Language 1	Language 2	Language 3	Language 4	Language 5	Language 1	Language 2	Language 3	Language 4	Language 5

\* Default Settings

Table 1

As can be seen from Table 1, in the preferred embodiment, the structure of the basic operating menu is generally organized based on selection categories. Each selection category further includes one or more selection command options. For example, the basic operating menu in the preferred embodiment has a Mode selection category which is labeled as selection category I in Table 1. The Mode selection category includes command options for: 1) "Copier", and 2) "Facsimile" modes which respectively allow the user to select the operating mode of the device

12 as either a copier or facsimile. In the "Copier" mode, the basic operating menu further includes: selection category II "Original Type"; selection category III "Maintenance"; selection category IV "Print Demo"; selection category V "Defaults"; and selection category VI "Language". Selection category II "Original Type" includes: command option 1 "Auto"; command option 2 "Text"; and command option 3 "Photo", which allow the user to input the type of original to be read by the reader. Selection category III "Maintenance" includes command options 1-5 which allow the user to select between five device maintenance functions as labeled in Table 1. Selection category V "Defaults" of the basic operating menu listed in Table 1 includes command options 1-5. The first four command options which include: command option 1 "Feature Defaults"; command option 2 "Program Time-out"; command option 3 "Sleep Mode"; and command option 4 "Paper Size" have two settings. The "Program Time-out", "Sleep Mode", and "Paper Size" command options have a default setting indicated by the \* symbol in Table 1. Selection category VI "Language" of the "Copier" mode listed in Table 1, includes command options 1-5 which allow the user to select the language used for displaying information on display 24 including the options of the operating menu.

The "Facsimile" mode of the basic operating menu listed in Table 1 includes substantially the same selection categories as the "Copier" mode of the basic menu. However, the "Facsimile" mode of the basic operating menu also includes selection category III "Telephone Numbers" comprising command options 1-8. This feature of the basic menu allows the user to automatically dial from up to, for example, eight telephone numbers stored in the memory 22 of the device 12. The features of the basic command menu listed in Table 1 are merely examples of the

type of features which may be available in the basic operating menu of the device 12. In alternate embodiments, the basic operating menu of the image transfer device may include more features or fewer features depending on device characteristics such as available memory space, capabilities of the CPU and size and type of the display. In other alternate embodiments, the structure of the basic operating menu of the device need not be as shown in Table 1, but rather any suitable organization of the basic operating menu features may be employed.

The CPU 20 displays the selection categories and command options of the basic operating menu listed in Table 1, as command buttons 52 on touch display 50 of the device 12. The command buttons 52 on the touch display 50 have indicia to indicate the selection category or command option corresponding to respective buttons 52. The command buttons corresponding to default settings of the operating menu (see Table 1) may appear when initially displayed in a manner to indicate to the user that the corresponding command options are default options. In the preferred embodiment, the selection categories of the basic operating menu (i.e. categories I-VI in Table 1) are generally displayed first. The command options within each category are hidden when the selection categories of the operating menu are displayed. To display the command options, if any, of a desired selection category on the display 50, the user touches the corresponding command button 52. The CPU 20 then changes the display 50 to show command buttons which represent the command options included in the selected category of the operating menu. In alternate embodiments, the structure of the basic operating menu may be displayed in any suitable manner such as



displaying one or more selection categories and their command options at the same time.

Referring now to Figs. 1 and 3, in accordance with one embodiment of the present invention, an enhanced program 210 for operating the image transfer device 12 is stored in the memory 22 of the device. (Similar reference numbers are used in Figs. 1, 3, 5 and 7 to designate similar features.) The enhanced program 210 includes a program 212 which defines an enhanced operating menu to be displayed by the CPU 20 on the touch portion 50 of the device display 24. Similarly to the default program 200, the enhanced program 210 also includes a program module 214 embodying instructions for the CPU 20 to control the functions of the image transfer device 12 corresponding to the commands within the enhanced operating menu in program module 212. As will be described in greater detail below, the enhanced program 210 is available for loading in the CPU 20 when the computer 14 is energized and connected via cable 36 to the connector 16A of the device 12. When the cable 36 is not connected to connector 16A, or the computer 14 is not energized, the enhanced program 210 stored in the memory 22A cannot be accessed or loaded in the CPU 20 of the device 12. Thus, the enhanced operating menu defined by program module 212 is available to be displayed by the CPU 20 on the display 50 of the device 12 when the computer 14 is energized and connected to the device 12. Otherwise, the basic operating menu in program module 202 of the default program 200 is available for display by the CPU 20.

In this embodiment, the connector 16A includes an electro-mechanical relay 60 or other suitable switching device. The relay 60 is adapted to be moved to the closed position, shown in Fig. 3, when the computer cable 36 is mated to the connector 16A and the computer 14 is

energized. Otherwise, the relay 60 in the connector 16A of the device 12 is in an open position (not shown). When the relay 60 is in the closed position, the CPU 20 becomes enabled to access and load the enhanced program 210 stored in the memory 22A of the device 12 thus making the enhanced operating menu in program module 212 available for display.

Fig. 4 is a flow chart which graphically illustrates the method for providing the device 12 with the enhanced operating menu. In block P1 of the flow chart in Fig. 4, the computer cable 36 is connected to the connector 16A of the device 12. In block P2, the computer 14 is energized. This enables the CPU 20 of the device 12 to display the enhanced operating menu on the display 50 of the device as illustrated in the flow chart of Fig. 4A. The starting condition in the flow chart of Fig. 4A, represented by  $\alpha$ , is that the computer 14 is connected via cable 36 to the device 12 and the computer 14 is energized. As stated earlier, the relay 60 in the connector 16A (see Fig. 3) moves to the closed position, block P3 of Fig. 4A, when the computer cable 36 is connected to the connector 16A and the computer is energized. The closing of the relay 16 enables the CPU 20 to now access and load the enhanced program 212 stored in the memory 22A of the device. Thus, in block P4 of Fig. 4A, the enhanced program 210 which includes program module 212 for displaying the enhanced operating menu is loaded in the CPU 20. Preferably, the CPU 20 has a loading program which automatically loads the enhanced program 210 from the memory 22A when the relay 60 is closed. Alternatively, after the relay is closed, the user may instruct the CPU via the user interface of the device to load the enhanced program from the memory module. After the enhanced program is loaded in the CPU 20, the enhanced operating menu defined by program module

0936495-0300  
660E20" 65649E60

212 is then available to be displayed on touch display 50 of the device 12. In the preferred embodiment, the user may select via a button on the touch display 50 or the user interface 26 whether the enhanced menu or the basic menu is to be displayed, though in alternate embodiments, the enhanced menu may be automatically displayed thereby replacing the basic menu on the display. Program module 214 included in the enhanced program 210 loaded in the CPU 20 provides program instructions to the CPU 20 so that the CPU is now capable of operating the device 12 according to the features of the enhanced operating menu.

One example of the features of the enhanced operating menu are listed in the Table 2 below.

I. MODE										
1. COPIER					2. FACSIMILE					
II. ORIGINAL TYPE					II. ORIGINAL TYPE					
1. AUTO*	2. TEXT	3. PHOTO			1. AUTO*	2. TEXT	3. PHOTO			
III. MAINTENANCE					III. TELEPHONE NUMBERS					
1. CLEAN PRINT HEAD	2. PRINT TEST PAGE	3. ALIGN PRINT HEAD	4. RESET PRINTER	5. INK LEVELS A. Black B. Cyan C. Magenta D. Yellow	No. 1	No. 2	No. 3	No. 4	No. 5	No. 6
					No. 7	No. 8	No. 9	No. 10	No. 11	No. 12
IV. PRINT DEMO										
V. DEFAULTS					V. DEFAULTS					
1. Feature Defaults A. Save new B. Reset	2. Program Time-out A. 60 sec.* B. 90 sec.	3. Sleep Mode A. 5 min* B. 10 min	4. Paper Size A. Letter* B. A4	5. Reset Factory	1. Feature Defaults A. Save new B. Reset	2. AUTO REDIAL A. 3 min* B. 5 min	2. Program Time-out A. 60 sec.* B. 90 sec.	3. Sleep Mode A. 5 min* B. 10 min	4. Paper Size A. Letter* B. A4	
VI. LANGUAGE					VI. LANGUAGE					
Language 1	Language 2	Language 3	Language 4	Language 5	Language 1	Language 2	Language 3	Language 4	Language 5	
VII. COLLATION					VII. COLLATION					
VIII. TIME & DATE STAMP					VIII. TIME & DATE STAMP					
IX. COMPANY NAME					IX. COMPANY NAME					
X. FIXED MESSAGE					X. FIXED MESSAGE					
XI. LOGO					XI. LOGO					
XII. PAGE NUMBERING					XII. PAGE NUMBERING					
XIII. WATERMARK					XIII. WATERMARK					

Table 2

The features of the enhanced operating menu listed in Table 2 are exemplary of the type of features which may be otherwise available to an image transfer device. In alternate embodiments, the enhanced operating menu of the device may include a greater or a fewer number of features than those listed in Table 2. As can be seen from Table 2, the enhanced operating menu of the image

transfer device 12 of the present invention has extended features which are not included in the basic operating menu listed in Table 1. In this case, the enhanced menu also includes generally all the features of the basic operating menu, though in alternate embodiments, the enhanced menu include only some of the features in the basic operating menu of the device. The extended features of the enhanced operating menu include: selection category VII "Collation"; selection category VIII "Time & Date" stamp; selection category IX "Company Name"; selection category X "Fixed Message"; selection category XI "Logo"; selection category XII "Page numbering"; and selection category XIII "Watermark". Also, the number of programmable telephone numbers has been expanded in comparison to the basic operating menu in Table 1. The enhanced operating menu may further include a printer and a scanner operating mode not shown in Table 2. Referring still to Figs. 1 and 3, the extended selection categories of the enhanced operating menu appear on the device display 50 as command buttons 52'. Command buttons 52 in the display 50 continue to represent the selection categories of the basic operating menu which are repeated in the enhanced menu being displayed.

In this embodiment of the present invention, some data used to effect image transfer with device 12 according to the enhanced menu features is stored in the memory 34A of the computer 14. By way of example, such data may include bitmaps representing time and date stamps, fixed messages, logos or watermarks to be added to the images as well as the coordinates for printing the bitmaps on sheet medium 102 (see Fig. 1). In addition, telephone numbers in excess of the number provided with the basic operating menu may also be stored in the computer memory 34A.

5  
10  
15  
20  
25  
30  
35

Referring now to Figs. 1 and 5, in accordance with a second embodiment of the present invention, the computer 14 of the image transfer system 10 has a processor 32B which is programmed to have a "Plug and Play" polling capability. "Plug and Play" polling allows the computer processor 32B to sense, by means of a polling signal, when the computer 14 is connected to the image transfer device 12 of the image transfer system. In this embodiment, the connector 16B of the device 12 need not include a relay to signal the device CPU 20 that the computer 14 is connected to the device 12. Rather, as illustrated in the flow chart of Fig. 6, in this embodiment when the computer processor 32B senses that the computer 14 is connected via cable 36 to the connector 16B of the device 12, block P5, the processor 32B sends an electronic signal to the device CPU 20, block P6. The electronic signal enables the CPU 20 to load the enhanced program 212 from the memory 22B of the device 12. For example, the CPU 20 may be programmed such that upon receiving the electronic signal from the computer 14, the CPU 20 is to initiate its loading program and load the enhanced program 210 from the device memory 22B. The CPU 20 does not load the enhanced program 210 until it receives the electronic signal from the computer 14. Alternatively, the computer processor 32B may be programmed to incorporate instructions in the electronic signal sent to the CPU 20, upon connection of the cable 36 to the device connector 16B, which instructions program the CPU 20 to load the enhanced program 210 from the device memory 22B. After the enhanced program 210 is loaded in the CPU 20, the enhanced operating menu in program module 212 is available for display on display 50 as described previously.

30

35

processor 32C to the device CPU 20. In this embodiment, the device CPU 20 may use the computer processor 32C, and memory 34C to effect some of the extended image transfer functions in the enhanced operating menu listed in Table 2. The CPU 20 may effect one or more of the extended image transfer command options of the enhanced operating menu of the image transfer device 12 using the following procedure. The reader 18 (see Fig. 1) is operated by the CPU 20 to read an image disposed on sheet medium 100. The CPU 20 then downloads the image data from the reader 18 to the computer processor 32C. In conjunction with this, the CPU 20 preferably also sends a signal to the computer processor 32C indicating which of the extended command options of the enhanced menu is to be performed. By way of example, the user may select from the enhanced menu to operate the device 12 in the copier mode with collation of copies (selection category VII in Table 2), and accordingly touches the appropriate command buttons on the touch display 50. The CPU 20 recognizes activation of these commands and sends a signal to the computer processor 32C indicating that collating function is to be performed. Upon receiving the image data downloaded by the CPU 20, the computer processor 32C automatically manipulates the image data in a manner consistent with effecting the selected image transfer function identified by the signal from the CPU 20. Then, the computer processor 32C automatically sends the now manipulated data back to the device 12 without user interaction. The CPU 20 routes the manipulated data to the print head 28 of the device 12 for printing on sheet medium 102, or to the communication device 30. For example, in the case of the collating function mentioned above, the computer processor 32C automatically stores the series of images read by the reader 18 and then generates sequential copies of the series of images in order to form a collated series of images in electronic



form. This step is performed by the processor 32C without user interaction to create the collated images. Then, the computer processor 32C automatically sends each series of images to the print head 28 of the device 12 also without user interaction. Each series of images received by the print head 28 is printed on sheet medium 102 to form printed collated images. In the case where the user chooses from the enhanced menu on display 50 to add a fixed message to printed copies, the computer processor 32C automatically merges the bitmap for the fixed message from the computer memory 34C with the image data downloaded from the reader 18 (see Fig. 1). The computer processor 32C automatically accesses the bitmap from the memory 34C and merges the bitmap with the image data without user interaction. The manipulated data is then automatically sent to the print head 28 without user interaction for printing the image and the fixed message on sheet medium 102.

The present invention provides a stand alone image transfer device equipped with minimal memory and processing capabilities to perform basic image transfer operations, which when connected to a computer such as a PC, can be quickly expanded to have an extended number of advanced function which generally are not available in an image transfer device of that size. The image transfer device in the present invention uses, to its advantage, the larger processing and memory capacity of the computer to carry out image transfer functions which otherwise could not be performed using only the in-built capabilities of the image transfer device.

The multi-function device 12 connectable to the PC 14, can operate, at least partially, as a stand alone device when not connected to the PC. The multi-function device 12 includes a printer, and/or a copier, and/or a

00334959-073099  
660620-65649660

facsimile and/or a optical scanner capability. For example, the device 12 may be able to function as a fax machine when not connected to the PC 14, but when connected to the PC it can function as both a fax machine and a computer printer. The PC 14 has the software and the memory which the device 12 uses, at least partially, to perform the new function.

In this invention, the device 12 has internal menu features as a stand alone unit, but when connected to the PC 14 extended menu features are now accessible/visible on the device control panel. The extended features disappear when the device is disconnected from the PC 14. One means for sensing connection and disconnection between the PC 14 and the device 12 is be using a cable 36 with USB (universal serial bus) connectors and "Plug & Play" polling. The internal menu features and possible sub-menu options are listed in Table 1. The list of extended menu features which can appear on the display of the device 12 when it is connected to the PC to become a fax/printer/copier with enhanced copier features is provided in Table 2. The extended menu features are not accessible or even visible on the display of the device when it is not connected to the PC.

The computer 14 has software to send instruction script to the device 12 when they are connected to each other to display the extended menu features, and software and memory of the PC to help execute those extended features. This invention provides the advantage of the device having internal minimal memory and menu displays to reduce the cost of the device, but uses or borrows the software and memory of the PC (without the user really knowing it, but he could) and add new user selectable/accessible/viewable menu functions to the control panel display 50 of the device 12. In addition

the PC 14 uploads a bitmap, such as a logo, an extra menu selection display feature for the bitmap, and coordinates for printing the bitmap on the paper. The upload would stay with the device 12 even if the PC 14 is disconnected from the device. This provides the advantage of faster printing of the indicia because the device 12 does not have to go back to the PC 14 for the indicia each time it is to be printed. Further variations of the indicia could be at the PC 14 and accessible by the menu display at the device 12 when the device is connected to the PC. Thus, when connected to the PC the user could select different variations of indicia such as selecting "Attorney - Client Privilege" (indicia 2) rather than "CONFIDENTIAL DOCUMENT" (indicia 1).

In this invention the extra menu functions can be stored in the device and merely enabled for viewing on the display 50 of the device 12 when connected to the PC 14. When not connected to the PC, the extra menu display of the features would still be in the memory of the device, but not accessible/viewable by the user (because they would not be able to be selected for use without connection to the PC). There is insufficient memory in the multifunction device to perform extended functions such as collation, but because the multifunction device 12 in this invention is attached to the PC 14, the user can scan the information of the reader 18, send the scanned data to the PC 14 to do the extended or enriched task, such as collation and reformat the document as a collated set of prints, and send the reformatted data and new instructions back to the multi-function (MF) device print head 24. Initiation of the job takes place at the device, so the user need not know the PC is involved in the process. That is, the device 12 is "smart" enough to know it has extra capabilities because a PC 14 is attached to it. This involves interaction with new

09364959-073099

5

10

25

30

It should be understood, that the foregoing description is only illustrative of the invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly,

the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

09364959-073093